

Features of Stainless Steel Cable Ties :-

- Easy Ball-locking design having Self-Locking mechanism
- Fully Rounded edges & Smooth Surfaces for safe handling
- 100% Stainless Steel construction - Body, Lock Head & Lock Ball SS316
- 360 degrees fully Polyester coated ties – Avoid galvanic corrosion
- Chemical & Weather resistant
- Non-Toxic & Halogen Free
- Long service life > 30 years (Install & Forget)
- Spectrum Multi Colored Ties – Electrical Phase Identification & Aesthetics



SS Cable Ties



Bands



Buckles



Identification & Marking System



Clamping Tools

CATERING TO WIDE RANGE OF INDUSTRIES

Communication



Refineries & Industries



Shipping



Oil & Petrochemical



Signages & Signals



Locomotive



Cable Installations



Automotive



Stainless Steel Cable Ties

Standard SS Cable Ties

Uncoated (AISI 316 Stainless Steel — Most Corrosive Environments)

CTE Part Code	Width		Length		Thickness		Min Loop		Max Bundle Dia		Std. Pkg. Qty
	(Inch)	(mm)	(Inch)	(mm)	(Inch)	(mm)	lbs	N	(Inch)	(mm)	
5S6-150-100	0.18	4.6	5	127	0.01	0.25	200	890	1	25	100
8S6-150-100	0.18	4.6	7.9	201	0.01	0.25	200	890	2	51	100
10S6-150-100	0.18	4.6	10.2	259	0.01	0.25	200	890	2.7	69	100
14S6-150-100	0.18	4.6	14.3	363	0.01	0.25	200	890	4	102	100
20S6-150-100	0.18	4.6	20.5	521	0.01	0.25	200	890	6	152	100
27S6-150-100	0.18	4.6	26.8	681	0.01	0.25	200	890	8	203	100
33S6-150-100	0.18	4.6	33	838	0.01	0.25	200	890	10	254	100
39S6-150-25	0.18	4.6	39.3	998	0.01	0.25	200	890	12	305	25
45S6-150-25	0.18	4.6	45.5	1156	0.01	0.25	200	890	14	356	25
50S6-150-25	0.18	4.6	49.2	1250	0.01	0.25	200	890	15	381	25
8S6-300-100	0.31	7.9	7.9	201	0.01	0.25	450	2000	2	51	50
14S6-300-100	0.31	7.9	14.3	363	0.01	0.25	450	2000	4	102	50
20S6-300-100	0.31	7.9	20.5	521	0.01	0.25	450	2000	6	152	50
27S6-300-100	0.31	7.9	26.8	681	0.01	0.25	450	2000	8	203	50
33S6-300-100	0.31	7.9	33	838	0.01	0.25	450	2000	10	254	50
45S6-300-25	0.31	7.9	45.5	1156	0.01	0.25	450	2000	14	356	25
17S6-600-50	0.5	12.7	17.1	434	0.01	0.25	600	2670	4	102	50
23S6-600-50	0.5	12.7	23.4	594	0.01	0.25	600	2670	6	152	50
30S6-600-50	0.5	12.7	29.7	754	0.01	0.25	600	2670	8	203	50
36S6-600-50	0.5	12.7	35.9	912	0.01	0.25	600	2670	10	254	50
42S6-600-25	0.5	12.7	42.2	1072	0.01	0.25	600	2670	12	305	25
17S6-900-50	0.63	15.9	17.1	434	0.015	0.38	900	4005	4	102	50
23S6-900-50	0.63	15.9	23.4	594	0.015	0.38	900	4005	6	152	50
30S6-900-50	0.63	15.9	29.7	754	0.015	0.38	900	4005	8	203	50
36S6-900-50	0.63	15.9	35.9	912	0.015	0.38	900	4005	10	254	50
42S6-900-25	0.63	15.9	42.2	1072	0.015	0.38	900	4005	12	305	25
COATED											
8SC6-150-100	0.18	4.6	7.9	201	0.01	0.25	100	445	2	51	100
14SC6-150-100	0.18	4.6	14.3	363	0.01	0.25	100	445	4	102	100
20SC6-150-100	0.18	4.6	20.5	521	0.01	0.25	100	445	6	152	100
27SC6-150-100	0.18	4.6	26.8	681	0.01	0.25	100	445	8	203	100
8SC6-300-50	0.31	7.9	7.9	201	0.01	0.25	250	1112	2	51	50
14SC6-300-50	0.31	7.9	14.3	363	0.01	0.25	250	1112	4	102	50
20SC6-300-50	0.31	7.9	20.5	521	0.01	0.25	250	1112	6	152	50
27SC6-300-50	0.31	7.9	26.8	681	0.01	0.25	250	1112	8	203	50